

Dual Wall Adhesive

- Shrink Temp. 194°F
- Flame Retardant
- Versatile & Economical Termination Solution
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices
- Excellent Electrical Properties
- Protects from Fluids, Moisture & Corrosion

2/1 and 3/1 Dual Wall Adhesive Heatshrink Tubing

Dual wall adhesive lined polyolefin heatshrink tubing is ideal for producing strong, weather tight seals on any heatshrink installation. During the application of heat from a heat gun or other heat source, the inner adhesive wall melts and flows, creating an adhesion layer to ensure a snug fit to your harness or connector.

Adhesive lined heatshrink comes in 2:1 and 3:1 shrink ratio, and it is available in 4' sticks.



Seals and protects a wide variety of electrical applications, including wire splices, breakouts, and connectors-to-cable transitions.



Shrinks to 1/2 it's original diameter

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Bulk Box Put Up/4' Pcs.	Shop Box Put Up/4' Pcs.	Available Colors	Lbs/10Pcs.
1/8"	H2A0.13	3.2mm	1.6mm	250	25	BK,CL	
1/4"	H2A0.25	6.4mm	3.2mm	250	25	BK,CL	
3/8"	H2A0.38	9.6mm	4.8mm	250	25	WH,BK,RD	
1/2"	H2A0.50	12.7mm	6.4mm	200	25	WH,BK,CL,RD	
3/4"	H2A0.75	19.1mm	9.6mm	80	25	WH,BK,RD	
1"	H2A1.00	25.4mm	12.7mm	50	25	WH,BK,RD	
1 1/2"	H2A1.50	38.1mm	19.1mm	15	5	BK	

Shrinks to 1/3 it's original diameter

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Bulk Box Put Up/4' Pcs.	Shop Box Put Up/4' Pcs.	Available Colors	Lbs/10Pcs.
1/4"	H3A0.25	6mm	2mm	250	25	WH,BK,CL,RD	0.35
3/8"	H3A0.38	9mm	3mm	250	25	WH,BK,CL,RD	0.55
1/2"	H3A0.50	12mm	4mm	200	25	WH,BK,CL,RD	0.75
3/4"	H3A0.75	19mm	6mm	80	25	WH,BK,CL,RD	1.65
1"	H3A1.00	24mm	8mm	50	25	WH,BK,CL,RD	2.15
2"	H3A2.00	50mm	17mm	15	5	WH,BK,CL,RD	5.25

