

Polyolefin

- Shrink Temp. 194°F
- Flame Retardant
- Versatile & Economical Termination Solution
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices

4:1 Polyolefin Heatshrink Tubing

4:1 Shrinkflex heatshrink tubing is the most versatile of the heatshrink products. The high shrink ratio ensures that the tubing will slip over large connectors or plugs and still provide a tight, professional seal.



Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/2"	H4N0.50BK	12.0mm	3.0mm	200'	25'	Black (BK)	1.17
3/4"	H4N0.75BK	19.0mm	4.5mm	200'	25'	Black (BK)	2.75
1"	H4N1.00BK	25.4mm	7.0mm	200'	25'	Black (BK)	3.25
1 1/4"	H4N1.25BK	32.0mm	8.0mm	200'	25'	Black (BK)	4.00
1 1/2"	H4N1.50BK	38.0mm	9.5mm	200'	25'	Black (BK)	4.25



PVC

Ultra Clear 2:1 PVC Heatshrink Tubing

Shrinks to 1/2 it's original diameter. Ultra clear PVC heatshrink tubing is ideal for application where complete transparency is required.

Perfect for protecting exposed wires and cables on motorcycles and custom automobiles. Resists gasoline, oil, and common chemicals; provides protection from abrasion and severe environments.



Stays clear when shrunk.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/4"	H2P0.25CL	6.4mm	3.2mm	200'	25'	Clear (CL)	0.60
5/16"	H2P0.31CL	8.0mm	4.0mm	200'	25'	Clear (CL)	0.70
3/8"	H2P0.38CL	9.5mm	4.8mm	200'	25'	Clear (CL)	0.80
1/2"	H2P0.50CL	12.7mm	6.4mm	200'	25'	Clear (CL)	1.10
5/8"	H2P0.63CL	15.9mm	7.9mm	200'	25'	Clear (CL)	1.16
3/4"	H2P0.75CL	19.1mm	9.5mm	200'	25'	Clear (CL)	1.90
1"	H2P1.00CL	25.4mm	12.7mm	200'	25'	Clear (CL)	3.00
2"	H2P2.00CL	50.8mm	25.4mm	100'	25'	Clear (CL)	

*Contact your Account Representative for heatshrink cutting & printing services.