

## Viton

- **Mil-I-DTL-23053/13**
- **Flame Retardant**



### 2/1 Viton® - Flexible Heatshrink Tubing

Viton is a rubber-like, highly fluid resistant, flame retardant fluoro-elastomer heatshrinkable tubing with high solvent resistance. The product is recommended for bundling, harnessing and environmental protection within engine compartments.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/8"	H2V0.13BK	3.2mm	1.6mm	100'	25'	Black (BK)	1.26
3/16"	H2V0.19BK	4.8mm	2.4mm	100'	25'	Black (BK)	1.45
1/4"	H2V0.25BK	6.4mm	3.2mm	100'	25'	Black (BK)	1.68
3/8"	H2V0.38BK	9.5mm	4.7mm	100'	25'	Black (BK)	2.27
1/2"	H2V0.50BK	12.7mm	6.4mm	100'	25'	Black (BK)	2.29
3/4"	H2V0.75BK	19.1mm	9.5mm	100'	25'	Black (BK)	4.14
1"	H2V1.00BK	25.4mm	12.7mm	100'	25'	Black (BK)	5.73

## Kynar

- **Mil-I-DTL-23053/8**
- **VW-1, UL 224, CSA**



### 2/1 Kynar® - Semi-Rigid Heatshrink Tubing

Kynar is a highly flame-retardant tubing that is tough and abrasion resistant in mechanical environments. The product is recommended for applications for strain relieving components such as soldered connections and splices.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Bulk Box Put Up/4'Pcs.	Shop Box Put Up/4'Pcs.	Available Colors	Lbs/10Pcs.
3/64"	H2K0.05CL	1.2mm	0.6mm	200	25	CL & BK	0.03
1/16"	H2K0.06CL	1.6mm	0.8mm	200	25	CL & BK	0.05
3/32"	H2K0.09CL	2.4mm	1.2mm	200	25	CL & BK	0.06
1/8"	H2K0.13CL	3.2mm	1.6mm	200	25	CL & BK	0.07
3/16"	H2K0.19CL	4.8mm	2.4mm	200	25	CL & BK	0.10
1/4"	H2K0.25CL	6.4mm	3.2mm	200	25	CL & BK	0.15
3/8"	H2K0.38CL	9.5mm	4.7mm	200	25	CL & BK	0.25
1/2"	H2K0.50CL	12.7mm	6.4mm	100	25	CL & BK	0.30
5/8"	H2K0.63CL	15.9mm	7.9mm	100	25	CL & BK	0.40
3/4"	H2K0.75CL	19.1mm	9.5mm	50	25	CL & BK	0.50
1"	H2K1.00CL	25.6mm	12.7mm	50	25	CL & BK	0.80

## Shield

- **Mil-I-DTL-23053/5**
- **Flame Retardant**
- **RoHS**



### 2/1 Shield Heatshrink Tubing

2/1 Shield heatshrink tubing is a unique combination of Polyolefin and conductive cloth, with a high frequency EMI shielding properties. This product, a flame retardant and fluid resistant tubing, is a perfect solution for protecting your wire & cable bundles.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Bulk Box Put Up/4'Pcs.	Shop Box Put Up/4'Pcs.	Available Colors	Lbs/10Pcs.
3/16"	H2C0.19BK	4.8mm	2.4mm	12	2	Black (BK)	0.31
1/4"	H2C0.25BK	6.4mm	3.2mm	12	2	Black (BK)	0.50
3/8"	H2C0.38BK	9.5mm	4.8mm	12	2	Black (BK)	0.63
1/2"	H2C0.50BK	12.7mm	6.4mm	12	2	Black (BK)	0.75
3/4"	H2C0.75BK	19.1mm	9.5mm	12	2	Black (BK)	1.00
1"	H2C1.00BK	25.4mm	12.7mm	12	2	Black (BK)	1.50
1 1/2"	H2C1.50BK	38.1mm	19.1mm	12	2	Black (BK)	2.25

800 323-5140  
[www.techflex.com](http://www.techflex.com)

Viton® is a registered trademark of DuPont Performance Elastomers.  
Kynar® is a registered trademark of the Arkema Corporation.

\*Contact your Account Representative for heatshrink cutting & printing services.